




TAPERED EQUIPMENT

Description	Gauge diameter		Dimensions of carbide mm		Flushing hole		Weight	Part No.
	mm	in	Height	Width	Side	Face		
Hex.22 7° tapered bit - Chisel bit (Horseshoe type)								
	32	1 1/4	13.5	8	2	-	0.22	1111-32722-13/8-40-13
	34	1 11/32	13.5	8	2	-	0.26	1111-34722-13/8-40-13
	36	1 7/16	13.5	8	2	-	0.29	1111-36722-13/8-40-13
	38	1 1/2	13.5	8	2	-	0.32	1111-38723-13/8-40-13
	38	1 1/2	15	9	2	-	0.32	1111-38723-15/9-40-13
	40	1 37/64	13.5	9.2	2	-	0.37	1111-40723-13/9-40-13
	40	1 37/64	13.5	9.2	2	-	0.37	1111-40723-13/9-40-12
	40	1 37/64	15	9.8	2	-	0.37	1111-40723-15/10-40-13
	40	1 37/64	15	9.8	2	-	0.37	1111-40723-15/10-40-12
	42	1 21/32	13.5	9.2	2	-	0.41	1111-42723-13/9-40-13
	42	1 21/32	13.5	9.2	2	-	0.41	1111-42723-13/9-40-12
	42	1 21/32	15	9.8	2	-	0.41	1111-42723-15/10-40-13
	42	1 21/32	15	9.8	2	-	0.41	1111-42723-15/10-40-12


Hex.22 7° tapered bit - Chisel bit (Oblique-chipways)

	30	1 3/16	13.5	8	2	-	0.21	1112-30722-13/8-42-22
	32	1 1/4	13.5	8	2	-	0.22	1112-32722-13/8-42-22
	34	1 11/32	13.5	8	2	-	0.26	1112-34722-13/8-42-22
	36	1 7/16	13.5	8	2	-	0.29	1112-36722-13/8-42-22
	38	1 1/2	15	9	2	-	0.33	1112-38723-15/9-42-22
	40	1 37/64	15	9.8	2	-	0.37	1112-40723-15/10-42-22
	42	1 21/32	15	9.8	2	-	0.41	1112-42723-15/10-42-22

Hex.22 7° tapered bit - Chisel bit (Flat-chipways)

	45	1 3/4	16	10	2	1	0.56	1113-45723-16/10-42-22
	50	1 31/32	16	10	2	1	0.61	1113-50723-16/10-42-22
	55	1 1/4	16	10	2	1	0.75	1113-55723-16/10-42-22
	60	2 23/64	16	10	2	1	0.86	1113-60723-16/10-42-22

TAPERED EQUIPMENT

Description	Gauge diameter		Dimensions of carbide mm		Flushing hole		Weight	Part No.
	mm	in	Height	Width	Side	Face		
Hex.22 7° tapered bit - Cross bit								
	32	1 1/4	12	8	2	1	0.26	1221-32722-12/8-42-23
	34	1 11/32	12	8	2	1	0.29	1221-34722-12/8-42-23
	36	1 7/16	12	8	2	1	0.32	1221-36722-12/8-42-23
	38	1 1/2	12	8	2	1	0.37	1221-38723-12/8-42-23
	40	1 37/64	12	8	2	1	0.4	1221-40723-12/8-42-23
	42	1 21/32	12	8	2	1	0.43	1221-42723-12/8-42-23
	45	1 3/4	14	8	2	1	0.49	1221-45723-14/8-42-23
	50	1 31/32	14	8	2	1	0.62	1221-50723-14/8-42-23
	55	2 1/4	16	10	2	1	0.82	1221-55723-16/10-42-23